ACRYLIC TENNIS COURT PAINT

CODE: 110040 REVISION: 02 DATE: 25 May 2026

GENERAL DESCRIPTION

A high quality water-based acrylic tennis court paint which dries to a smooth matt, durable finish.

USES AND PROPERTIES

For tennis courts, netball courts, basketball courts and general multi-sport recreational surfaces. Suitable for properly prepared concrete, cementitious and asphalt surfaces.

TECHNICAL DATA

Binder Type		:	Acrylic, Co-polymer Emulsion
Drying Time	Surface Dry	:	<1 hour (at 23°C and 50% humidity)
	Hard Dry	:	<4 hours (at 23°C and 50% humidity)
Drying Process		:	Water evaporation / coalescence
Overcoating		:	>4 hours
Viscosity		:	98 - 101KU
Specific Gravity		:	1,213 - 1,263 kg/litre
Mass Non-Volatile Content		:	38 - 42% (±3%)
Volume Solids		:	24 - 28% (±3%)
Gloss		:	Matt Finish
Coverage		:	5 - 6m²/litre
Dry Film Thickness		:	45 - 55 microns @ 5 - 6m²/litre
Colour Range		:	Tennis Court Green and selected court colours
Clean Equipment With		:	Water
Pack Sizes		:	5 litre, 20 litre

Coverage/spreading rate of **Acrylic Tennis Court Paint** depends largely on the condition and porosity of the substrate being painted and the manner in which the product is applied.

APPLICATION

All surfaces must be clean and in sound condition.

Remove all oil, dirt, grease, flaking paint and contamination. Fill cracks and holes in the surface as outlined in this technical data sheet.

Improperly prepared surfaces may result in coating failure.

Do not apply when ambient temperatures are <4°C or >40°C.

New surfaces

- Remove dust, dirt, laitance and plaster splashes. Cut out large cracks and imperfections. Fill and sand smooth when dry.
- For new concrete, dilute the first coat with clean water at a ratio of 1 part paint to 1 part water and apply as a penetrating primer/sealer coat.
- Allow diluted primer/sealer coat to dry for at least 4 hours before overcoating.
- Apply 2 full coats of **Acrylic Tennis Court Paint**. Allow at least 4 hours' drying time between coats.

Technical Data Sheet

ACRYLIC TENNIS COURT PAINT

APPLICATION (continued)

Previously coated surfaces

- Remove loose paint completely by scraping or wire brushing.
- Fill all large cracks and imperfections and Profill. Allow to dry and sand smooth when dry.
- Ensure surface is sound, clean and dry.
- Apply a suitable acrylic primer where required, or use **Acrylic Tennis Court Paint** diluted 15% with clean water on porous areas. Allow to dry.
- Apply 2 full coats of **Acrylic Tennis Court Paint**. Allow at least 4 hours' drying time.

SAFETY INSTRUCTIONS

Always keep out of reach of children and animals.
Wear a suitable dust mask and goggles when preparing surfaces.
Ensure good ventilation during application and drying.
If accidental contact with skin, wash immediately with soap and water or a recognised skin cleaner.
If accidental contact with eyes, rinse immediately with plenty of water and seek medical advice.
Harmful if swallowed. Seek medical attention and do not induce vomiting.

GENERAL

Different surfaces and environmental conditions require specific painting systems to produce the best possible results.
It is therefore recommended that you contact a Dekro Sales representative for advice on all your painting requirements whenever possible.

PREVENTING PROBLEMS AND GENERAL INFORMATION

IMPORTANT: Concrete, cement plaster and masonry surfaces must be dry before painting and should not exceed a moisture content of 10% as measured with a suitable moisture meter. The ambient temperature must be between 4°C and 40°C and humidity between 10% and 85%.

Excessive application thickness and/or rapid drying could lead to mud cracking.
Avoid applying under adverse weather conditions as this could result in poor product performance.

Suitable primers must be used where applicable.
Work from corner to corner, or from a natural cut off point to another.
Do not attempt touch ups, but redo complete panels.

Always keep a wet edge and avoid downing tools during the application process to prevent lap marks and variances in colour or texture.

To ensure consistent appearance ensure that the batch numbers on all containers used are the same. Where batch numbers on containers differ, intermix containers before use.

Technical Data Sheet

ACRYLIC TENNIS COURT PAINT

CLEANING, STORAGE AND DISPOSAL

Remove as much paint as possible from application equipment and wash immediately after use with water.
Close containers tightly after use and store in a cool well-ventilated area.
Do not empty contents or wash water into drains or water courses.
When disposing please follow local authorities regulations and recycle the container after use.
Avoid storing in direct sunlight and heat.

Technical Data Sheet

APPLICATIONS FOR AFRICA™

DEKRO
IS THE ARCHITECTS CHOICE

The technical data furnished is given to the best of our knowledge based on controlled laboratory tests under ideal application conditions. No guarantee of any performance characteristic is therefore given or implied and we do not hold ourselves responsible for any consequential damage of whatsoever nature that may arise from use of our products. In the event of a proven product fault our liability will be limited to the replacement of the product only. It is the user's responsibility to confirm the currency of product data sheets.