CEMENT REMOVER

PRODUCT CODE: 096103

TYPICAL USE

Dekro Cement Remover is an acid based solution which is used for the removal of dried cement and mortar.

APPLICATION

Put on rubber gloves to protect hands.
Cement Remover is ready for use but may be thinned up to 50% with water if desired.
(Always add Cement Remover to water).
Apply by brush, sponge or by carefully pouring on the affected area.
Allow 10 – 15 minutes to react then remove it with a scraper, wire brush or Scotchbrite pad.
Re-apply a second application if necessary.
Finally, rinse well with water.

TECHNICAL DATA

Coverage	:	-10 – 15m²/litre - depends on the thickness of the cement.
Clean up:	Water.	
Flash Point	:	N/A
Pack Size	:	1 litre, 5 litre plastic bottles.

x

RECAUTIONS

Always wear acid resistant gloves and avoid contact with Cement Remover.
Refer to the Material Safety Data Sheet for details of safety.
Never store product in a metal container as it will react.
It must be stored in plastic.

The technical data furnished is obtained from controlled laboratory tests under ideal application conditions. No guarantee of any performance characteristic is therefore given or implied and we do not hold ourselves responsible for any consequential damage of whatsoever nature that may arise from use of our products. In the event of a proven fault our liability will be limited to the replacement of the product only. It is the users responsibility to confirm the currency of product data sheets