HYDROWASH FUNGICIDAL

CODE: 308001 REVISION: 02 DATE: 09 December 2025

GENERAL DESCRIPTION

General purpose biocide for sterilising surfaces prior to painting.

USES AND PROPERTIES

Hydrowash Fungicidal is a broad-spectrum biocide developed for sterilising surfaces prior to painting. Suitable for eliminating mould, yeast and algae growths, and their spores prior to application of hygiene, roof and general coating systems. It is supplied ready for use and contains a dye to assist with ensuring all affected areas are treated during application.

TECHNICAL DATA

Binder Type	:	N/A
Drying Time	:	N/A
Drying Process	:	Water evaporation
Overcoating	:	24 hours – wash surface well to remove dead spores before overcoating
Viscosity	:	10 - 15“ Ford Cup No. 4
Specific Gravity	:	0,999 ±0,025kg/litre
Mass Non-Volatile Content	:	1% ±0,2%
Volume Solids	:	1% ±0,2%
Coverage	:	<10m²/litre (best applied with backpack spray bottle)
Colour Range	:	Transparent Blue
Clean Equipment With	:	Water
Pack Sizes	:	5 litre, 25 litre

Coverage/spreading rate of **Hydrowash Fungicidal** depends largely on the condition and porosity of the substrate being painted and manner in which the product is applied.

Technical Data Sheet

APPLICATION

Correct surface preparation is essential for good product performance and all surfaces should be prepared as per the standard Dekro Preparation Specifications. Copies of these are available on request from Dekro Paints or can be downloaded from our website –www.dekro.co.za.
Do not apply when ambient temperatures are <4°C or >40°C.
Apply **Hydrowash Fungicidal** by brush or backpack or general-purpose spray bottle at the specified spread rate.
Allow 24 hours reaction time to kill all spores before rinsing with clean water.
In areas with very dense growth, it is recommended to apply a second coat and allow it to dry before applying your finishing coats.

HYDROWASH FUNGICIDAL

SAFETY INSTRUCTIONS

Always keep out of reach of children and animals.
Wear a suitable dust mask and goggles when preparing surfaces.
Ensure good ventilation during application and drying.
If accidental contact with skin, wash immediately with soap and water or a recognised skin cleaner.
If accidental contact with eyes, rinse immediately with plenty of water and seek medical advice.
Harmful if swallowed. Seek medical attention and do not induce vomiting.

GENERAL

Different surfaces and environmental conditions require specific painting systems to produce the best possible results.
It is therefore recommended that you contact a Dekro Sales representative for advice on all your painting requirements whenever possible.

PREVENTING PROBLEMS AND GENERAL INFORMATION

IMPORTANT: Walls (cement plaster, concrete or masonry) must be dry before painting and should not exceed a moisture content of 10% as measured with a Protimeter Surveymaster Moisture Meter or equal.
The ambient temperature must be between 4ºC and 40ºC and humidity between 10% and 85%.
Avoid applying under adverse weather conditions as this could result in poor product performance.

CLEANING, STORAGE AND DISPOSAL

Remove as much paint as possible from application equipment and wash immediately after use with water.
Close containers tightly after use and store in a cool well-ventilated area.
Do not empty contents or wash water into drains or water courses.
When disposing please follow local authorities' regulations and recycle the container after use.
Avoid storing in direct sunlight and heat.

Technical Data Sheet

APPLICATIONS FOR AFRICA™

DEKRO
IS THE ARCHITECTS CHOICE

The technical data furnished is given to the best of our knowledge based on controlled laboratory tests under ideal application conditions. No guarantee of any performance characteristic is therefore given or implied and we do not hold ourselves responsible for any consequential damage of whatsoever nature that may arise from use of our products. In the event of a proven product fault our liability will be limited to the replacement of the product only. It is the user's responsibility to confirm the currency of product data sheets.