PAINTER'S PAL
PAINT & ACCESSORIES

ALL-IN-ONE WATERPROOFING



THE LAST WATERPROOFING PRODUCT YOU WILL EVER BUY









ALL-IN-ONE WATERPROOFING

USES AND PROPERTIES:
Painter's Pal All-in-One Waterproofing is PU Acrylic Polyurethane Dispersion with a slight sheen for waterproofing of roofs, parapets and wall surfaces

TECHNICAL DATA:

Binder Type	**PU Acrylic Polyurethane Dispersion**
Drying Time	**Surface Dry: 1 -2 hours (at 23°C and 50% humidity) Hard Dry: 24 hours (at 23°C and 50% humidity)**
Drying Process	**Water evaporation followed by heat cure**
Over coating	**>4 hours**
Viscosity	**120 - 130 KU**
Specific Gravity	**1,13 ±0,05kg/litre**
Non-Volatile Content	**65% ±3%**
Volume	**60% ±3%**
Gloss	**Satin Sheen**
Coverage	**1 -4m²/litre**
Dry Film Thickness	**300 microns @ 2m²/litre**
Thin With	**Water**
Clean Equipment With	**Water**
Colour Range	**Black, White and Stone Grey**
Pack Sizes	**Pack Sizes : 5, 20ltr**

SCAN FOR

TECHNICAL DATA SHEET

Coverage/spreading rate of Painter's All-in-One Waterproofing depends largely on the condition and porosity of the substrate being painted and manner in which the product is applied.

Correct surface preparation is essential for good product performance and all surfaces should be prepared as per the standard Dekro Preparation Specifications.
Copies of these are available on request from your Dekro Paints or can be downloaded from our website –www.dekro.co.za.
Do not apply when ambient temperatures are <4°C or >40°C. After correct surface preparation, then stir thoroughly
and apply a minimum of 2 coats of Painter's Pal Braai Paint by brush, roller or spray at the specified spread rate. Allow to dry before over coating as per technical data.

ALL-IN-ONE- COMMON PROBLEMS AND SOLUTIONS

PAINT ADHESION ISSUES
POOR PREPARATION AND CLEANING OF SURFACE OR LATENT MOISTURE. REMOVE BACK TO SUBSTRATE AND REPEAT PROCESS

PINHOLES
PRODUCT NOT APPLIED TO ENCAPSULATE MEMBRANE COMPLETELY. APPLY ADDITIONAL COATS UNTIL NO PINHOLES ARE VISIBLE

PAINT DELAMINATION
POOR PREPARATION. POOR SURFACE CONDITIONS. REMOVE PAINT BACK TO SUITABLE SUBSTRATE AND REPEAT PROCESS

DEKRO PAINTS 24 FABRIEK STREET KUILS RIVER
INFO@DEKRO.CO.ZA WWW.DEKRO.CO.ZA 0800 222 423 (TOLL FREE)

APPLICATIONS FOR AFRICA®