PAINTER'S PAL
PAINT & ACCESSORIES

STICK TO ANYTHING

WATERBASED COATING THAT WILL STICK TO ANYTHING





USES AND PROPERTIES:
Painter's Pal Stick to Anything is a ready to use quick-drying glossy enamel, designed for application to various substrates, (new and old), based on a multi-phase, self-crosslinking, pure acrylic dispersion.

TECHNICAL DATA:

Binder Type	**Self-crosslinking multiphase Modified Acrylic coating**
Drying Time	**Surface Dry: <1/2 hour (at 23°C and 50% humidity) Hard Dry: <2 hours (at 23°C and 50% humidity)**
Drying Process	**Solvent Evaporation / Coalescing**
Over coating	**>3 hours**
Viscosity	**90- 100 KU**
Specific Gravity	**1,2 ±0,05kg/litre**
Non-Volatile Content	**45% ±3%**
Volume	**48% ±3%**
Gloss	**Gloss**
Coverage	**8 - 10m²/litre**
Dry Film Thickness	**40 microns @ 8m²/litre**
Clean Equipment With	**Water**
Colour Range	**White and Standard Colours**
Pack Sizes	**Pack Sizes : 1ltr, 5Ltr**

SCAN FOR

TECHNICAL DATA SHEET

Coverage/spreading rate of Painter's Pal Stick to Anything depends largely on the condition and porosity of the substrate being painted and manner in which the product is applied.

STICK TO ANYTHING

STICK TO ANYTHING - COMMON PROBLEMS AND SOLUTIONS

PAINT ADHESION ISSUES
POOR PREPARATION AND CLEANING OF SURFACE. REMOVE BACK TO SUBSTRATE AND REPEAT PROCESS

SUITABLE SURFACE
ALWAYS CHECK SUITABILTY OF SURFACE BY COMPLETING A SMALL SECTION AND ALLOW TO DRY

PAINT DELAMINATION
POOR PREPARATION. POOR SURFACE CONDITIONS. REMOVE PAINT BACK TO SUITABLE SUBSTRATE AND REPEAT PROCESS

Correct surface preparation is essential for good product performance and all surfaces should be prepared as per the standard Dekro Preparation Specifications.
Copies of these are available on request from your Dekro Paints or can be downloaded from our website –www.dekro.co.za.
Do not apply when ambient temperatures are <4°C or >40°C. After correct surface preparation, then stir thoroughly
and apply a minimum of 2 coats of Painter's Pal Braai Paint by brush, roller or spray at the specified spread rate. Allow to dry before over coating as per technical data.

DEKRO PAINTS 24 FABRIEK STREET KUILS RIVER
INFO@DEKRO.CO.ZA WWW.DEKRO.CO.ZA 0800 222 423 (TOLL FREE)

APPLICATIONS FOR AFRICA®