DEKRO PAINTS

SUPER ACRYLIC

WATERBASED MATT FINISH
PURE ACRYLIC COATING

SUPER ACRYLIC

Waterbased Matt Finish Coating
For Interior Walls

SUPER ACRYLIC

Waterbased Matt Finish Coating
For Exterior Walls





USES AND PROPERTIES:
Dekro Super Acrylic is a superior quality washable matt coating based on an adhesion promoted emulsion.

TECHNICAL DATA:

Binder Type	**Adhesion promoted 100% pure acrylic**
Drying Time	**Surface Dry: <1 hours (at 23°C and 50% humidity)** **Hard Dry : <4 hours (at 23°C and 50% humidity)**
Drying Process	**Water evaporation**
Over coating	**>6 hours**
Viscosity	**105 - 110KU**
Specific Gravity	**1,56 ±0,05kg/litre**
Non-Volatile Content	**61% ±3%**
Volume	**40% ±3%**
Gloss	**Matt**
Coverage	**8m²/ltr**
Dry Film Thickness	**50 microns @ 8m²/litre**
Colour Range	**White & Pastel, Deep and Clear Colours**
Pack Sizes	**Pack Sizes : 1ltr, 5ltr, 20ltr**

SCAN FOR

TECHNICAL DATA SHEET

Coverage/spreading rate of Dekro Super Acrylicdepends largely on the condition and porosity of the substrate being painted and manner in which the product is applied.

Correct surface preparation is essential for good product performance and all surfaces should be prepared as per the standard Dekro Preparation Specifications.
Copies of these are available on request from your Dekro Paints or can be downloaded from our website –www.dekro.co.za.
Do not apply when ambient temperatures are <4°C or >40°C. After correct surface preparation, prime with the recommended primer, then stir thoroughly and apply a minimum of 1 coat of Vasbyt Single Pack Metal Etch Primer by brush, roller or spray at the specified spread rate. Allow to dry before over coating as per technical data.

SUPER ACRYLIC

SUPER ACRYLIC - COMMON PROBLEMS AND SOLUTIONS

PAINT ADHESION ISSUES

INCORRECT PREPERATION AND CLEANING. REMOVE BACK TO SUITABLE SUBSTRATE AND REPEAT PROCESS. USE SUITABLE PRIMERS.

BUBBLES FORMING IN COATING

MOISTURE RELATED ISSUES WITHIN THE SUBSTRATE. RESOLVE ISSUES AND REPEAT THE PROCESS.

PAINT DELAMINATION

POOR PREPARATION. POOR SURFACE CONDITIONS. REMOVE PAINT BACK TO SUITABLE SUBSTRATE AND REPEAT PROCESS. USE SUITABLE PRIMERS.

DEKRO PAINTS 24 FABRIEK STREET KUILS RIVER
INFO@DEKRO.CO.ZA WWW.DEKRO.CO.ZA 0800 222 423 (TOLL FREE)

APPLICATIONS FOR AFRICA®