

PRODUCT DESCRIPTION

An environmentally friendly, specially formulated Acrylic coating incorporating long-strand inert fibres which ensure flexibility and strength. Has a slight sheen finish.

COLOUR RANGE

White

PACKAGING

5 litre and 20 litre

RECOMMENDED FOR

EXTERIOR surfaces.

Used as an intermediate, high-build coating for bridging hairline cracks on exposed plastered surfaces. Suitable for weatherproofing tops of exposed plastered walls window sills, small ledges and tops of plaster mouldings, as well as exposed weather-facing walls or fairfaced brick walls.

Suitable for areas where Fibreglass tissue is not suitable.

NOTE: Midas Fibreforce is an intermediate coating and must be overcoated with Midas Midalux 240, Midas Flexicryl or Midas Coast Guard.

NOT RECOMMENDED FOR

Not suitable for the treatment of rising damp.

APPLICATION

PLEASE NOTE: Correct preparation is essential. All surfaces must be sound and prepared in the recommended manner. For more information on surface preparation contact your nearest Paintsmiths store.

After the correct surface preparation has been completed apply the necessary primer coat.

Then thoroughly stir and apply two coats of Midas Fibreforce to suitably primed surfaces using a brush or a roller at the stipulated spread rates. Always lay off with a brush.

As it is a thick coating always ensure that the coating has dried in depth before overcoating.

Apply two coats of a recommended topcoat. Refer to the relevant product datasheets for spread rates and overcoating times.

SPREAD RATE

±3m²/litre

1.5m²/litre (2 coats) severe situations

NOTE: The spread rates quoted are approximate and should only be used as a guide as the actual rate will vary depending on the condition and porosity of the substrate.

OVERCOATING TIME

> 6 hours

NOTE: It is very important that overcoating times, as set out for the various products, are adhered to and also that the prevailing weather conditions are taken into account. Ambient and substrate temperatures, humidity and wind etc., can influence drying times of all coatings.

Performance problems can occur if any of the previous coats have not been allowed to dry properly before being overcoated.

IMPORTANT: To prevent surface contamination, coatings must not be left longer than 48 hours between coats. If environmental or weather conditions have caused surface contamination, all surfaces must be thoroughly washed down before applying the next coating.

CLEANERS/SOLVENTS

Water

PREVENTING PROBLEMS AND GENERAL INFORMATION

IMPORTANT: All substrates must be dry before painting and should not exceed a moisture content of 10% as measured with a Protimeter Surveymaster Moisture Meter or equal. The ambient temperature must not be below 10°C and not higher than 35°C.

Humidity must not be below 10% and not higher than 85%.

· Always lay off the coating with a brush to spread out the fibres.

SHELF LIFE

When filled, the product is sterile, and unopened has a shelf life of at least 12 months from the date of manufacture.

ENVIRONMENTAL NOTE

Please note: Disposal of paint containers and/or contents other than in an approved manner may result in contamination of our water ways or the pollution of our environment. Do not clean equipment where water and solvents will enter storm water drains. Please dispose of unused paint and paint containers through an approved recycling scheme or seek advice from our local council about other accepted disposal method. For more information on our environmental policies, enquire in store.

VOC GREEN FILTER

The information herein provided is based upon our current theoretical compositions/calculations, and current data from our raw material suppliers. We thus reserve the right to amend and correct when/if necessary.

FOOTNOTE

The above information is intended as a guide only. Since this product is applied by 3rd parties, Paintsmiths and the manufacturer cannot be held liable for any loss or damage whatsoever relating to application or to the surface to which it is applied. Paintsmiths and the manufacturer reserve the right to make changes at any time, without notice.



TECHNICAL DATA



Viscosity	112 - 115PP
Specific Gravity	1,371 g/ml (±0,05)
pH	8.5 - 9.0
Weight Solids Content	64% (±5%)
Fineness of grind	Bit free
Volume Solids Content	51% (±5%)
Pigment Volume Concentration	38% (±5%)
Spread Rate	3m ² /litre
Dry Film Thickness	120 microns
Sheen 20°	Matt
Sheen 60°	Matt
Sheen 85°	Matt
(on glass @ 100 microns WFT after 24 hours)	
Surface Dry	<1 hour
Hard Dry	<4 hours
Overcoating	>6 hours
Diluent/Cleaning	Water
Application Temperatures	>10° <35°
Storage Temperatures	>5° <35°
Shelf Life in unopened containers	12 months
VOC rating	Minimal VOC >1 <3 g/litre
Drying Mechanism	Water evaporation followed by coalescence
Scrubs	N/A
Vehicle Type	Styrene Acrylic
Pigment Type	Rutile Titanium
Application	Brush or roller

All tests are performed at 23°C and 50% relative humidity.

Contact your nearest store for Technical Advice should you require any further information.

Safety Datasheets are available on request.

* This VOC value is determined on the untinted base. However, as Midas use ZERO VOC stainers for all their tinting, the VOC contribution from these is minimal and will vary from colour to colour.

ENVIRONMENTAL NOTE

Please note: Disposal of paint containers and/or contents other than in an approved manner may result in contamination of our water ways or the pollution of our environment. Do not clean equipment where water and solvents will enter storm water drains. Please dispose of unused paint and paint containers through an approved recycling scheme or seek advice from our local council about other accepted disposal method. For more information on our environmental policies, enquire in store.

VOC GREEN FILTER

The information herein provided is based upon our current theoretical compositions/calculations, and current data from our raw material suppliers. We thus reserve the right to amend and correct when/if necessary.

FOOTNOTE

The above information is intended as a guide only. Since this product is applied by 3rd parties, Paintsmiths and the manufacturer cannot be held liable for any loss or damage whatsoever relating to application or to the surface to which it is applied. Paintsmiths and the manufacturer reserve the right to make changes at any time, without notice.

MIDAS EARTHCOTE

24 FABRIEK STREET INDUSTRIAL KUILS RIVER 7580

021 931 3131

www.paintsmiths.co.za