

OMNISKIM INTERIOR/EXTERIOR

MIDAS
ENVIROLITE

JUNE 2026 / V1

PRODUCT DESCRIPTION

An environmentally friendly, interior and exterior, multi-purpose, ready-mixed filler that dries to a matt finish. Developed as a scraper coat for plastered walls to fill in surface imperfections prior to painting. Can be sanded once fully dried.

COLOUR RANGE

Light cream when dry.

PACKAGING

8 kg, 30 kg

RECOMMENDED FOR

INTERIOR and EXTERIOR surfaces.

Midas Omniskim Interior/Exterior can also be used for skimming uneven surfaces, filling hairline cracks and general touch up applications typically required of most surfaces prior to the painting of walls and ceilings.

NOT RECOMMENDED FOR

Not suitable for repairing of deep crack more than 2mm. Use a suitable crack filler prior to the skimming application.

APPLICATION

PLEASE NOTE: Correct preparation is essential. All surfaces must be sound and prepared in the recommended manner. For more information on surface preparation contact your closest Paintsmiths store.

Stir well prior to application. Should any thinning be required, a small amount of water may be added and thoroughly mixed into Midas Omniskim Interior/Exterior. To avoid any pinhole formation in the skim film it is recommended that any porous, friable or crumbling surfaces are first treated with Midas Cemproof prior to skimming. Apply Midas Omniskim Interior/Exterior in a thin layer using a rust-free steel smooth edge plasterers skimming trowel or paint scraper. If the area being repaired requires a thick layer application, several thin coats may be required with each coat being allowed to dry thoroughly before the next coat is applied. Omniskim Interior/Exterior will shrink back slightly in deep holes and imperfections

The final coat must then be sanded to achieve the required finish using 100 grit or finer sandpaper. Prior to painting any dust from sanding process must be removed by wiping down the surface with a damp cloth (not wet) and allowed to dry. Surfaces may be painted 6 – 9 hours (overnight drying is preferable) after application of Midas Omniskim Interior/Exterior with a suitable Acrylic topcoat. Provided the surfaces are sanded correctly and all the powder has been wiped off and the surfaces are free of any contamination, then a primer is not necessarily required.

However, as a safeguard a suitable primer is generally recommended before applying finishing coats.

SPREAD RATES

On reasonable plaster $\pm 1\text{m}^2/\text{kg}$ as a skim coat and $2\text{m}^2/\text{kg}$ as a scraper coat.

NOTE: The spread rates quoted are approximate and should only be used as a guide as the actual rate will vary depending on the condition and porosity of the substrate.

OVERCOATING TIMES

6 - 9 hours (overnight drying is preferable)

NOTE: It is essential to adhere to overcoating times, as specified for our various products. Prevailing weather conditions must be considered as ambient and substrate temperatures, humidity and wind etc., will influence drying time. Performance problems can occur if any of the previous coats have not been allowed to dry properly before being overcoated.

CLEANERS/SOLVENTS

Water

PREVENTING PROBLEMS AND GENERAL INFORMATION

IMPORTANT: All substrates must be dry before painting and should not exceed a moisture content of 10% as measured with a Protimeter Surveymaster Moisture Meter or equal. The ambient temperature must not be below 10°C and not higher than 35°C. Humidity must not be below 10% and not higher than 85%.

- Surfaces must be dry, firm and free of flaking paint, dust, mould, oil, grease, wax polish and organic growth
- Organic growth must be removed and the spores killed with Midas Fungicidal Wash.
- Porous, friable and chalking surfaces should be removed as much as possible and then primed with a coat of Midas Cemproof prior to the skimming application. The surfaces treated with the Midas Cemproof must be touch dry ± 1 hour prior to skimming.
- Nail heads, unless non-rusting, should be touched with paint or Midas Cemproof prior to application.
- Sand when dry (minimum of 4 hours after application depending on thickness). 100 grit or finer sandpaper is recommended.
- Not suitable for use over structural cracks and expansion joints.

SHELF LIFE

Store product in a cool, dry environment (below 25°C). Excess humidity or damp can result in the cement starting to cure, causing bitterness in the product or the bag solidifying.

ENVIRONMENTAL NOTE

Please note: Disposal of paint containers and/or contents other than in an approved manner may result in contamination of our water ways or the pollution of our environment. Do not clean equipment where water and solvents will enter storm water drains. Please dispose of unused paint and paint containers through an approved recycling scheme or seek advice from our local council about other accepted disposal method. For more information on our environmental policies, enquire in store.

VOC GREEN FILTER

The information herein provided is based upon our current theoretical compositions/calculations, and current data from our raw material suppliers. We thus reserve the right to amend and correct when/if necessary.

FOOTNOTE

The above information is intended as a guide only. Since this product is applied by 3rd parties, Paintsmiths and the manufacturer cannot be held liable for any loss or damage whatsoever relating to application or to the surface to which it is applied. Paintsmiths and the manufacturer reserve the right to make changes at any time, without notice.



MIDAS EARTHCOTE

24 FABRIEK STREET INDUSTRIAL KUILS RIVER 7580

021 931 3131

www.paintsmiths.co.za

TECHNICAL DATA

Viscosity	135 - 138PP
Specific Gravity	1,72 (±0,01)
pH	8,5 - 9,0
Weight Solids Content	69,2% (±5%)
Fineness of grind	Bit free
Volume Solids Content	47,0% (±5%)
Pigment Volume Concentration	82,0% (±5%)
Spread Rate	±3m ² /kg @ 0.2mm thickness (depending on surface conditions)
	±1m ² /kg as a skim coat
	±2m ² /kg as a scraper coat
Dry Film Thickness	1m ² /kg
	±581µ wet film
	±273µ dry film
Sheen 20°	N/A
Sheen 60°	N/A
Sheen 85°	N/A
(on glass @ 100 microns WFT after 24 hours)	
Surface Dry	1-4 hours @ 25 degrees C (depending on thickness)
Hard Dry	6-9 hours @ 25 degrees C
Overcoating	>9 hours (overnight drying is preferable)
Diluent/Cleaning	Water
Application Temperatures	>10° <35°
Storage Temperatures	>5° <35°
Shelf Life in unopened containers	12 months
VOC rating	Zero VOC <1 g/litre*
Drying Mechanism	Water evaporation and coalescence
Scrubs	N/A
Vehicle Type	Styrene Acrylic
Pigment Type	N/A
Application	Trowel or paint scraper



All tests are performed at 23°C and 50% relative humidity.
Contact your nearest store for Technical Advice should you require any further information. Safety Datasheets are available on request.

* This VOC value is determined on the untinted base. However, as Paintsmiths use ZERO VOC stainers for all their tinting, the VOC contribution from these is minimal and will vary from colour to colour.

ENVIRONMENTAL NOTE

Please note: Disposal of paint containers and/or contents other than in an approved manner may result in contamination of our water ways or the pollution of our environment. Do not clean equipment where water and solvents will enter storm water drains. Please dispose of unused paint and paint containers through an approved recycling scheme or seek advice from our local council about other accepted disposal method. For more information on our environmental policies, enquire in store.

VOC GREEN FILTER

The information herein provided is based upon our current theoretical compositions/calculations, and current data from our raw material suppliers. We thus reserve the right to amend and correct when/if necessary.

FOOTNOTE

The above information is intended as a guide only. Since this product is applied by 3rd parties, Paintsmiths and the manufacturer cannot be held liable for any loss or damage whatsoever relating to application or to the surface to which it is applied. Paintsmiths and the manufacturer reserve the right to make changes at any time, without notice.