

PRODUCT DESCRIPTION

A clear, slightly gel-like blend of Methylene Chloride and other solvents and surfactants. It is both non-acidic and non-caustic.

COLOUR RANGE

Clear.

PACKAGING

1 litre and 5 litre metal tins.

RECOMMENDED FOR

INTERIOR and EXTERIOR surfaces.

Used for removing alkyd-based paints and varnishes from most substrates.

NOT RECOMMENDED FOR

Not ideal for removing PVA and Acrylic paints.

APPLICATION

PLEASE NOTE: Correct preparation is essential. All surfaces must be sound and prepared in the recommended manner. For more information on surface preparation contact your nearest Paintsmiths store.

Apply a thick coat of Paint Remover with a brush using a dabbing action. Do not brush out. Allow the product to react with the paint.

When the paint starts to wrinkle and lift, remove all softened paint with a scraper. Several applications may be required depending on the age of the coating and the number of coats. It is important to remove all traces of Paint Remover with soap and water, and dry before doing the necessary preparation and repainting.

When dealing with heavy/thick paint layers, cover the applied Paint Remover with a plastic sheet to prevent the solvent from evaporating.

SPREAD RATE

N/A

OVERCOATING TIME

N/A

CLEANERS/SOLVENTS

Wipe excess paint from brushes, rollers and spray equipment using an absorbent cloth before washing with water.

PREVENTING PROBLEMS AND GENERAL INFORMATION

IMPORTANT: Walls (cement plaster, concrete or masonry) must be dry before painting and should not exceed a moisture content of 10% as measured with a Protimeter Surveymaster Moisture Meter or equal. The ambient temperature must not be below 10°C and not higher than 35°C.

Humidity must not be below 10% and not higher than 85%.

- Excessive application thickness and/or rapid drying could lead to mud cracking.
- Avoid applying under adverse weather conditions as this could result in poor product performance.
- Always keep a wet edge and avoid downing tools during application to prevent lap marks and variances in colour or texture.
- Work from corner to corner, or from a natural cut off point to another.
- Do not attempt touch ups but redo complete panels.

SHELF LIFE

When filled, the product is sterile, and unopened has a shelf life of at least 12 months from the date of manufacture.

ENVIRONMENTAL NOTE

Please note: Disposal of paint containers and/or contents other than in an approved manner may result in contamination of our water ways or the pollution of our environment. Do not clean equipment where water and solvents will enter storm water drains. Please dispose of unused paint and paint containers through an approved recycling scheme or seek advice from our local council about other accepted disposal method. For more information on our environmental policies, enquire in store.

VOC GREEN FILTER

The information herein provided is based upon our current theoretical compositions/calculations, and current data from our raw material suppliers. We thus reserve the right to amend and correct when/if necessary.

FOOTNOTE

The above information is intended as a guide only. Since this product is applied by 3rd parties, Paintsmiths and the manufacturer cannot be held liable for any loss or damage whatsoever relating to application or to the surface to which it is applied. Paintsmiths and the manufacturer reserve the right to make changes at any time, without notice.

TECHNICAL DATA

Viscosity	90 - 95KU
Specific Gravity	1,194 (±0,05)
pH	N/A
Weight Solids Content	4% (±5%)
Fineness of Grind	Lump free
Volume Solids Content	5% (±5%)
Pigment Volume Concentration	N/A
Spread Rate	N/A
Dry Film Thickness	N/A
Sheen 20°	N/A
Sheen 60°	N/A
Sheen 85°	N/A
(on glass @ 100 microns WFT after 24 hours)	
Surface Dry	N/A
Hard Dry	N/A
Overcoating	N/A
Diluent/Cleaning	Water
Application Temperatures	>10°C <35°C
Storage Temperatures	>5°C <35°C
Shelf Life in unopened containers	12 months
Drying Mechanism	N/A
Application	Brush

All tests are performed at 23°C and 50% relative humidity.
Contact your nearest store for Technical Advice should you require any further information.
Safety Datasheets are available on request.

ENVIRONMENTAL NOTE

Please note: Disposal of paint containers and/or contents other than in an approved manner may result in contamination of our water ways or the pollution of our environment. Do not clean equipment where water and solvents will enter storm water drains. Please dispose of unused paint and paint containers through an approved recycling scheme or seek advice from our local council about other accepted disposal method. For more information on our environmental policies, enquire in store.

VOC GREEN FILTER

The information herein provided is based upon our current theoretical compositions/calculations, and current data from our raw material suppliers. We thus reserve the right to amend and correct when/if necessary.

FOOTNOTE

The above information is intended as a guide only. Since this product is applied by 3rd parties, Paintsmiths and the manufacturer cannot be held liable for any loss or damage whatsoever relating to application or to the surface to which it is applied. Paintsmiths and the manufacturer reserve the right to make changes at any time, without notice.

MIDAS EARTHCOTE

24 FABRIEK STREET INDUSTRIAL KUILS RIVER 7580

021 931 3131

www.paintsmiths.co.za